Distributed by:

JAMECO® ELECTRONICS

**www.Jameco.com ✦ 1-800-831-4242**

The content and copyrights of the attached material are the property of its owner.

Weller®

# NT Series Tips for WMP Micro Soldering Pencil

**Jameco Part Number 233576**
**(NT1X)**




## The Weller Advantage

- The heating element is contained in the pencil rather than the tip so you don't throw away a good heater every time you wear out a tip
- **Gives you substantial savings on tip costs compared to the competition**




### Micro

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NT1 | 0.010 | 0.25 | -- | -- | 0.291 | 7.40 |
| NT1S | 0.010 | 0.25 | -- | -- | 0.333 | 8.45 |




### Bent Round

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NT1X | 0.016 | 0.40 | 0.063 | 1.60 | 0.321 | 8.15 |




### Round

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NT4 | 0.047 | 1.20 | -- | -- | 0.390 | 9.90 |




### Chisel

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NT6 | 0.063 | 1.60 | 0.016 | 0.40 | 0.372 | 9.45 |
| NTA | 0.063 | 1.60 | 0.016 | 0.40 | 0.331 | 8.40 |
| NTB | 0.094 | 2.40 | 0.031 | 0.80 | 0.289 | 7.35 |
| NTC | 0.126 | 3.20 | 0.031 | 0.80 | 0.305 | 7.75 |
| NTD | 0.157 | 4.00 | 0.031 | 0.80 | 0.305 | 7.75 |
| NTH | 0.031 | 0.80 | 0.016 | 0.40 | 0.331 | 8.40 |
| NTK | 0.047 | 1.20 | 0.016 | 0.40 | 0.331 | 8.40 |




### Bent Chisel

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NTAX | 0.063 | 1.60 | 0.031 | 0.80 | 0.339 | 8.61 |




### Cylindrical

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NTGW | 0.079 | 2.00 | 0.118 | 3.00 | 0.528 | 13.40 |




### SMT Blade

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NTSMT01 | 0.410 | 10.41 | 0.022 | 0.56 | 0.280 | 7.11 |
| NTSMT02 | 0.620 | 16.75 | 0.022 | 0.56 | 0.280 | 7.11 |
| NTSMT03 | 0.820 | 20.83 | 0.022 | 0.56 | 0.280 | 7.11 |




### SMT Slot

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NTSMT04 | 0.070 | 1.78 | 0.195 | 4.95 | 0.070 | 1.78 |
| NTSMT05 | 0.060 | 1.52 | 0.090 | 2.29 | 0.070 | 1.78 |
| NTSMT06 | 0.100 | 2.54 | 0.068 | 1.73 | 0.055 | 1.40 |
| NTSMT07 | 0.090 | 2.29 | 0.190 | 4.53 | 0.070 | 1.78 |




### SMT Tunnel

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NTSMT08 | 0.180 | 4.57 | 0.200 | 5.08 | 0.090 | 2.29 |
| NTSMT09 | 0.410 | 10.41 | 0.200 | 5.08 | 0.090 | 2.29 |
| NTSMT10 | 0.450 | 11.49 | 0.270 | 6.86 | 0.090 | 2.29 |
| NTSMT11 | 0.520 | 13.21 | 0.375 | 9.53 | 0.125 | 3.18 |
| NTSMT12 | 0.620 | 15.75 | 0.375 | 9.53 | 0.125 | 3.18 |
| NTSMT13 | 0.720 | 18.27 | 0.375 | 9.53 | 0.125 | 3.18 |
| NTSMT14 | 0.740 | 18.80 | 0.365 | 9.02 | 0.125 | 3.18 |




### SMT Quad

| Cat. No. | A in. | A mm | B in. | B mm | C in. | C mm |
|---|---|---|---|---|---|---|
| NTSMT15 | 0.105 | 2.67 | 0.303 | 7.70 | 0.150 | 3.81 |
| NTSMT16 | 0.410 | 10.41 | 0.410 | 10.41 | 0.150 | 3.81 |
| NTSMT17 | 0.500 | 12.70 | 0.500 | 12.70 | 0.150 | 3.81 |
| NTSMT18 | 0.540 | 13.72 | 0.340 | 8.60 | 0.150 | 3.81 |
| NTSMT19 | 0.750 | 19.05 | 0.750 | 19.05 | 2.350 | 5.96 |
| NTSMT20 | 0.915 | 23.24 | 0.680 | 17.27 | 0.150 | 3.81 |
| NTSMT21 | 0.965 | 24.51 | 0.965 | 24.51 | 2.350 | 5.96 |
| NTSMT22 | 1.155 | 29.59 | 1.165 | 29.59 | 2.350 | 5.96 |